

Compact Sushi Machine SSF-JXA







CE EK

SSF-JXA-CE

Easy operation, Easy Cleaning, Consistent & Quality Nigiri Sushi

Simple design for easy operation & maintenance.

Suzumo's technique allows for stable and fluffy Nigiri Sushi without cutting the rice grains.

- Simple operation with buttons for counter reset & adjustments of weight, softness & speed.
- Simple structure reduces daily cleaning time & keeps sanitation.
- Better quality by refined Rice Supply unit, Vertical Weighing unit, and Forming unit.



Fuji Keizai [Labour shortage and Potential Demand & Consideration on Automated Robots] Results for 2022 Sales Quantity and Value for Sushi Making Robot





Dimensions Power cable (2m)Turn table Hopper lid 330 477 Rice hopper Operation panel EMO switch **8 A** (CE model only) 000000 Safety cover Main power switch Hopper lid rack (Option)

Specifications

Model	SSF-JXA-AS
	SSF-JXA-CE
	(Applied to CE & UKCA Regulation)
Input	AC220-240V 50/60Hz Power cable: 2m
Power rating	110W
Capacity	2000, 2400, 2800pcs/hr (selectable)
Weight per piece	18, 20, 22, 25g (selectable)
Hopper capacity	Approx 5.5Kg of cooked rice
	(Including supply hopper unit)
Dimensions	330W×477D×584Hmm

Weight	25kg
Dimension of	TypeA: 55L×24Wmm
rice ball	(More rounded at the top of rice ball)
(Selectable mold	TypeB: 55L×25Wmm
units)	(Oval shape)
Hardness setting	Soft ⇔ Hard (7steps adjustment)
Option	Hopper lid rack

Suzumo Machinery Co., Ltd.

Global Business Division

Tel. +81 3-3993-1407 e-mail overseas@suzumo.co.jp URL https://www.suzumokikou.com/

< Contact in Singapore >

Suzumo Singapore Corporation Pte. Ltd.

Tel. +65 6254-2080 e-mail sales@suzumo-sg.com



YouTube

雅麗盈設備有限公司 APEX NOBLE EQUIPMENT LTD

^{*} Designs and specifications are subject to change without notice.

^{*} While capacity expresses the machine's performance capabilities, it is predicated upon the machine being operated correctly.